

WS-C3560CX-12TC-S Catalyst Compact switch

Model: WS-C3560CX-12TC-S | Brand: CISCO

Product Overview

3560-CX Switch 12 GE, uplinks: 2 x 1G SFP and 2 x 1G copper, IP Base

Product page: <https://www.linknewnet.com/products/ws-c3560x-12tc-s>

Quick Specifications

Attribute	Value
Ethernet Ports	12 x 10/100/1000 Gigabit Ethernet
PoE Output Ports	12 PoE+
Available PoE Power	240W
Uplinks	2 x 1G copper plus 2 x 10G SFP+
Default Software	IP Base (IP Services with RTU License)
Powering Option	Internal power supply
Available PoE Power (W)	240W
Can Switch Be Powered with Uplinks?	No
Forwarding Bandwidth	34 Gbps
Flash memory	128 MB
Memory DRAM	512 MB
Max VLANs	1023
VLAN IDs	4000
Maximum transmission unit (MTU)	Up to 9000 bytes
Jumbo frames	9198 bytes
Forwarding rate 64 Byte Packet	50.6 mpps
Dimensions (H x W x D)	1.75 x 10.6 x 9.4 in (4.44 x 26.9 x 23.8 cm)
Weight	5.1 lb (2.31 Kg)
Operating altitude	Up to 3048 m (Up to 10,000 ft)
Storage altitude	Up to 4000 m (Up to 15,000 ft)
Product Code	WS-C3560CX-12TC-S
Brand	CISCO

Replacement / Alternative Options

If the WS-C3560CX-12TC-S is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-C3560-24TS-E	CiscoCatalyst 3560 24 10/100 + 2 SFP Enhanced Image

WS-C3550-24-DC-SMI	Cisco Catalyst 3550 Series Switch WS-C3550-24-DC-SMI 24-10/100+2GBIC ports
--------------------	--

Request availability: [Ask for current stock](#) of WS-C3560CX-12TC-S or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).