

WS-C6509-E Catalyst 6500 Enhanced 9-slot chassis 15RU

Model: WS-C6509-E | Brand: CISCO

Product Overview

Catalyst 6500 Enhanced 9-slot chassis, 15RU, no PS, no Fan Tray

Product page: <https://www.linknewnet.com/products/ws-c6509-e>

Quick Specifications

Attribute	Value
Number of Slots	9
With Supervisor Engine 720-10 GE	12.2(33)SXH
Module Compatibility	All modules based on the software release in the system
With Supervisor Engine 720	12.2(14)SX
Inches	24.5 x 17.5 x 18.2
With Supervisor Engine 2T-10 GE	15.0(1)SY
With Supervisor Engine 32	12.2(18)SXF
Centimeters	62.2 x 44.5 x 46.0
Rack Units (RU)	14
Chassis Only (lbs)	60
Fully Configured (lbs)	190
Input Voltage	100 to 240 VAC -48 to -60 VDC
Operating Temperature	32°F to 104°F (0 to 40°C)
Storage Temperature	-4 to 149°F (-20 to 65°C)
Thermal Transition	0.5°C per minute (hot to cold) 0. 33°C per minute (cold to hot)
Relative Humidity	Ambient (noncondensing) operating: 5% to 90% Ambient (noncondensing) nonoperating and storage: 5% to 95%
Operating Altitude	Certified for operation: 0 to 6500 ft (0 to 2000 m) Designed and tested for operation: -200 to 10,000 ft (-60 to 3000 m)
Product Code	WS-C6509-E
Brand	CISCO

Replacement / Alternative Options

If the WS-C6509-E is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-C6503-E-FWM-K9	Cisco Catalyst switch 6503E Firewall Security System
WS-C6503E-CSM	CSM, 6503, Sup720 Bundle

Request availability: [Ask for current stock](#) of WS-C6509-E or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).