

WS-X4013+10GE- Cisco Catalyst 4500 Supervisor Engine

Model: WS-X4013+10GE | Brand: CISCO

Product Overview

Catalyst 4500 Supervisor Engine II+10GE, 2x10GE (X2) and 4x1GE (SFP)

Product page: <https://www.linknewnet.com/products/ws-x4013-10ge>

Quick Specifications

Attribute	Value
Type	Catalyst 4500 Supervisor Engine II+10GE
Ports	2x 10GE (X2) and 4x 1GE (SFP)
Switching Capacity	136 Gbps
Forwarding Rate	102 Mpps
Layer Support	Layer 2 and Layer 3
Redundancy	Supports Supervisor Engine redundancy
Flash Memory	64 MB
DRAM	512 MB
IPv6 Support	Yes
QoS	Yes, supports advanced QoS features
VLAN Support	Yes, up to 4096 VLANs
Dimensions	13.56 x 1.75 x 16.41 inches
Power Consumption	175W
Operating Temperature	0°C to 40°C
Storage Temperature	-40°C to 70°C
Operating Humidity	10% to 90%, non-condensing
Compliance	FCC Part 15 Class A, EN55022 Class A
Management	SNMP, CLI, CiscoWorks
Uplink Interfaces	2x 10GE
Network Interfaces	4x 1GE
Product Code	WS-X4013+10GE
Brand	CISCO

Replacement / Alternative Options

If the WS-X4013+10GE is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-X4013+	Cisco Catalyst 4500 Series Switch Module WS-X4013+ 4500 Supervisor Engine II-Plus (IOS), 2GE,Console(RJ-45)

WS-X4013+TS	Catalyst 4503 Supervisor Engine SupII-Plus-TS, 12 10/100/1000 PoE+8 SFP slots
-------------	---

Request availability: [Ask for current stock](#) of WS-X4013+10GE or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).